



Landscape Seeder Specifications

Turfmaker III Series

Product Attributes	SL-3081	SLP-3081	SL-3101	SLP-3101	SL-3121	SLP-3121
Approximate Weight	2,438 lbs. (1,097 kg)	2,101 lbs. (945 kg)	2,840 lbs. (1,278 kg)	2,481 lbs. (1,116 kg)	3,259 lbs. (1,467 kg)	2,906 lbs. (1,308 kg)
Working Width	8 ft. 0 in. (2.4 m)	8 ft. 0 in. (2.4 m)	10 ft. 0 in. (3.0 m)	10 ft. 0 in. (3.0 m)	12 ft. 0 in. (3.6 m)	12 ft. 0 in. (3.6 m)
Transport Width	11 ft. 5 in. (3.43 m)	9 ft. 6 in. (2.85 m)	13 ft. 5 in. (4.03 m)	11 ft. 4 in. (3.4 m)	15 ft. 6 in. (4.65 m)	13 ft. 3 in. (3.98 m)
Transport Height	6 ft. 6 in. (1.98 m)	Tractor Dependent	6 ft. 6 in. (1.98 m)	Tractor Dependent	6 ft. 6 in. (1.98 m)	Tractor Dependent
Road Clearance	1 ft. 3 in. (0.38 m)	Tractor Dependent	1 ft. 3 in. (0.38 m)	Tractor Dependent	1 ft. 3 in. (0.38 m)	Tractor Dependent
Overall Height	5 ft. 3 in. (1.6 m)	4 ft. 5 in. (1.35 m)	5 ft. 3 in. (1.6 m)	4 ft. 5 in. (1.35 m)	5 ft. 3 in. (1.6 m)	4 ft. 5 in. (1.35 m)
Overall Length	11 ft. 9 in. (3.58 m)	7 ft. 1 in. (2.14 m)	11 ft. 9 in. (3.58 m)	7 ft. 1 in. (2.14 m)	11 ft. 9 in. (3.58 m)	7 ft. 1 in. (2.14 m)
Seed Box	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover
Seed Box Capacity - Meter Box	15 bu. (529 l)	15 bu. (529 l)	19 bu. (670 l)	19 bu. (670 l)	23 bu. (810 l)	23 bu. (810 l)
Seed Meters	High Capacity Meter	High Capacity Meter	High Capacity Meter	High Capacity Meter	High Capacity Meter	High Capacity Meter
Seed Meter Drive	Ground Driven	Ground Driven	Ground Driven	Ground Driven	Ground Driven	Ground Driven
Seed Meter Spacing	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)	4.25 in. (108 mm)
Seed Delivery	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray
Pulverizer Roller - Front	15.75 in. (400 mm) Gray Cast Iron	15.75 in. (400 mm) Gray Cast Iron	15.75 in. (400 mm) Gray Cast Iron	15.75 in. (400 mm) Gray Cast Iron	15.75 in. (400 mm) Gray Cast Iron	15.75 in. (400 mm) Gray Cast Iron
Pulverizer Roller - Rear	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron
Pulverizer Axle Bearings	Greaseable	Greaseable	Greaseable	Greaseable	Greaseable	Greaseable
Pulverizer Axle Size - Front	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)	12.75 in. (324 mm)
Pulverizer Axle Size - Rear	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)
Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch	Pull-Type with Hydraulic Transport	Three-Point Hitch - Cat. II Free Link; Cat. II, IIIN Quick Coupler Hitch
Hydraulic Equipment	Cylinders with Hoses to Hitch Point	N/A	Cylinders with Hoses to Hitch Point	N/A	Cylinders with Hoses to Hitch Point	N/A
Tire Size	9.5L x 15-8 Ply Implement Rib	N/A	11L x 15-12 Ply Implement Rib	N/A	11L x 15-12 Ply Implement Rib	N/A
S-Tine Wheel Track Remover	Optional	Optional	Optional	Optional	Optional	Optional
Coil Tine Track Remover	Optional	Optional	Optional	Optional	Optional	Optional
Front Roller Scraper Kit	Optional	Optional	Optional	Optional	Optional	Optional
Turfmaker Sprockets	Optional	Optional	Optional	Optional	Optional	Optional
Electronic Acre Meter	Optional	Optional	Optional	Optional	Optional	Optional
Seed Shaft Monitor Kit	Optional	Optional	Optional	Optional	Optional	Optional
Safety Warning Lights & SMV Emblem	Standard	Standard	Standard	Standard	Standard	Standard
Safety Chain Kit	Standard	N/A	Standard	N/A	Standard	N/A
Powder Coat Paint, Red	Standard	Standard	Standard	Standard	Standard	Standard
Horsepower Requirements	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.	6 to 8 HP (4.5 to 6 kW) per ft.
Recommended Operating Speed	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)	3 to 6 MPH (5 to 10 km/h)