



2400 Series Weatherproofer (WP1) Specifications

3 Row Coil Tine Harrow Attachment

Adapts To:	2410-6-24	2410-7-24	2410F-7-24	2410AFG-7-24	2410-9-24	2410F-9-24	2410AFG-9-24	2430-11-24	2430-13-24
Approximate Weight	1,197 lbs. (543 kg)	1,253 lbs. (568 kg)	1,253 lbs. (568 kg)	1,253 lbs. (568 kg)	1,420 lbs. (644 kg)	1,680 lbs. (762 kg)	1,680 lbs. (762 kg)	1,950 lbs. (885 kg)	2,100 lbs. (953 kg)
Tines	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)	0.625 in. x 30 in. (15.9 x 762 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Distance Between Bars	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Coil Tine Protection	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs
Section Width	8 ft. (2.4 m) -- 8 ft. (2.4 m)	8 ft. (2.4 m) -- 10 ft. (3.0 m)	6 ft. (1.8 m) -- 6 ft. (1.8 m)	6 ft. (1.8 m) -- 6 ft. (1.8 m)	10 ft. (3.0 m) -- 10 ft. (3.0 m)	8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m)	8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m)	6 ft. (1.8 m) -- 14 ft. (4.3 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 14 ft. (4.3 m) -- 8 ft. (1.8 m)