

| Product Attributes                       | 6250-40   | 6250-45   | 6250-50   |
|--|---|---|---|
| <b>24 IN. BLADES ON 7 IN. SPACING</b>    |   |   |   |
| Approximate Weight                       | 36,445 lbs. (16,531 kg)   | 39,180 lbs. (17,772 kg)   | 41,945 lbs. (19,026 kg)   |
| Working Width                            | 40 ft. 6 in. (12.3 m)   | 44 ft. 2 in. (13.5 m)   | 49 ft. 6 in. (15.1 m)   |
| Front Gang Width                         | 38 ft. 2 in. (11.6 m)   | 41 ft. 10 in. (12.7 m)  | 47 ft. 0 in. (14.3 m)   |
| Transport Width                          | 17 ft. 6 in. (5.3 m)  | 17 ft. 6 in. (5.3 m)  | 17 ft. 6 in. (5.3 m)  |
| Transport Height                         | 11 ft. 10 in. (3.6 m)   | 12 ft. 3 in. (3.7 m)  | 13 ft. 6 in. (4.1 m)  |
| Number of Blades - Front Gang            | 66  | 74  | 82  |
| Number of Blades - Rear Gang             | 68  | 76  | 84  |
| Blade Size                               | 24 in. (610 mm) x 0.25 in. (6.35 mm)<br>24 in. (610 mm) x 0.25 in. (6.35 mm) Rollable | 24 in. (610 mm) x 0.25 in. (6.35 mm)<br>24 in. (610 mm) x 0.25 in. (6.35 mm) Rollable | 24 in. (610 mm) x 0.25 in. (6.35 mm)<br>24 in. (610 mm) x 0.25 in. (6.35 mm) Rollable |
| Blade Concavity                          | Low Concavity   | Low Concavity   | Low Concavity   |
| Blade Spacing - Front Gang               | 7 in. (178 mm)  | 7 in. (178 mm)  | 7 in. (178 mm)  |
| Blade Spacing - Rear Gang                | 7 in. (178 mm)  | 7 in. (178 mm)  | 7 in. (178 mm)  |
| <b>24 IN. BLADES ON 8.75 IN. SPACING</b> |   |   |   |
| Approximate Weight                       | 34,210 lbs. (15,517 kg)   | 36,715 lbs. (16,654 kg)   | 37,960 lbs. (17,218 kg)   |
| Working Width                            | 40 ft. 4 in. (12.3 m)   | 44 ft. 4 in. (13.5 m)   | 50 ft. 0 in. (15.2 m)   |
| Front Gang Width                         | 38 ft. 0 in. (11.6 m)   | 42 ft. 0 in. (12.8 m)   | 47 ft. 6 in. (14.5 m)   |
| Transport Width                          | 17 ft. 6 in. (5.3 m)  | 17 ft. 6 in. (5.3 m)  | 17 ft. 6 in. (5.3 m)  |
| Transport Height                         | 11 ft. 10 in. (3.6 m)   | 12 ft. 3 in. (3.7 m)  | 13 ft. 6 in. (4.1 m)  |
| Number of Blades - Front Gang            | 56  | 62  | 68  |
| Number of Blades - Rear Gang             | 58  | 64  | 70  |
| Blade Size                               | 24 in. (610 mm) x 0.25 in. (6.35 mm)<br>24 in. (610 mm) x 0.25 in. (6.35 mm) Rollable | 24 in. (610 mm) x 0.25 in. (6.35 mm)<br>24 in. (610 mm) x 0.25 in. (6.35 mm) Rollable | 24 in. (610 mm) x 0.25 in. (6.35 mm)<br>24 in. (610 mm) x 0.25 in. (6.35 mm) Rollable |
| Blade Concavity                          | Regular Concavity   | Regular Concavity   | Regular Concavity   |
| Blade Spacing - Front Gang               | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   |
| Blade Spacing - Rear Gang                | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   |
| <b>26 IN. BLADES ON 8.75 IN. SPACING</b> |   |   |   |
| Approximate Weight                       | 36,035 lbs. (16,345 kg)   | 38,740 lbs. (17,572 kg)   | 40,200 lbs. (18,234 kg)   |
| Working Width                            | 40 ft. 4 in. (12.3 m)   | 44 ft. 4 in. (13.5 m)   | 50 ft. 0 in. (15.2 m)   |
| Front Gang Width                         | 38 ft. 0 in. (11.6 m)   | 42 ft. 0 in. (12.8 m)   | 47 ft. 6 in. (14.5 m)   |
| Transport Width                          | 17 ft. 6 in. (5.3 m)  | 17 ft. 6 in. (5.3 m)  | 17 ft. 6 in. (5.3 m)  |
| Transport Height                         | 11 ft. 10 in. (3.6 m)   | 12 ft. 3 in. (3.7 m)  | 13 ft. 6 in. (4.1 m)  |
| Number of Blades - Front Gang            | 56  | 62  | 68  |
| Number of Blades - Rear Gang             | 58  | 64  | 70  |
| Blade Size                               | 26 in. (660 mm) x 0.25 in. (6.35 mm)<br>26 in. (660 mm) x 0.3125 in. (7.94 mm)        | 26 in. (660 mm) x 0.25 in. (6.35 mm)<br>26 in. (660 mm) x 0.3125 in. (7.94 mm)        | 26 in. (660 mm) x 0.25 in. (6.35 mm)<br>26 in. (660 mm) x 0.3125 in. (7.94 mm)        |
| Blade Concavity                          | Regular Concavity   | Regular Concavity   | Regular Concavity   |
| Blade Spacing - Front Gang               | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   |
| Blade Spacing - Rear Gang                | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   | 8.75 in. (222 mm)   |
| Blade Scrapers                           | 4.5 in. (114 mm) Adjustable   | 4.5 in. (114 mm) Adjustable   | 4.5 in. (114 mm) Adjustable   |
| Blade Scraper Mount                      | Heavy-Duty 0.5 in. (12.7 mm) Steel Spring Arm   | Heavy-Duty 0.5 in. (12.7 mm) Steel Spring Arm   | Heavy-Duty 0.5 in. (12.7 mm) Steel Spring Arm   |

| Product Attributes                                  | 6250-40   | 6250-45   | 6250-50   |
|---|---|---|---|
| Gang Spools - Front Gang                            | 5.5 in. (140 mm) Diameter, 0.25 in. (6.35 mm) Wall Weldment | 5.5 in. (140 mm) Diameter, 0.25 in. (6.35 mm) Wall Weldment | 5.5 in. (140 mm) Diameter, 0.25 in. (6.35 mm) Wall Weldment |
| Gang Spools - Rear Gang                             | 5.5 in. (140 mm) Diameter, 0.25 in. (6.35 mm) Wall Weldment | 5.5 in. (140 mm) Diameter, 0.25 in. (6.35 mm) Wall Weldment | 5.5 in. (140 mm) Diameter, 0.25 in. (6.35 mm) Wall Weldment |
| Gang Angle - Front Gang                             | 20 Degree   | 20 Degree   | 20 Degree   |
| Gang Angle - Rear Gang                              | 18 Degree   | 18 Degree   | 18 Degree   |
| Gang Shaft  | 1.75 in. (44.5 mm) Round                                    | 1.75 in. (44.5 mm) Round                                    | 1.75 in. (44.5 mm) Round                                    |
| Gang Bearings                                       | C-Cushion Trunnion Mount with Greaseable Triple Lip Seals   | C-Cushion Trunnion Mount with Greaseable Triple Lip Seals   | C-Cushion Trunnion Mount with Greaseable Triple Lip Seals   |
| Frame Construction                                  | Laser Cut/Matchcut Components, Robotically Welded           | Laser Cut/Matchcut Components, Robotically Welded           | Laser Cut/Matchcut Components, Robotically Welded           |
| Transport Lift Axles                                | 5.5 in. (140 mm) with UHMW Maintenance Free Pivots          | 5.5 in. (140 mm) with UHMW Maintenance Free Pivots          | 5.5 in. (140 mm) with UHMW Maintenance Free Pivots          |
| Transport Axle Type                                 | Walking Tandems with Maintenance Free Pivots                | Walking Tandems with Maintenance Free Pivots                | Walking Tandems with Maintenance Free Pivots                |
| Tire Size - Center Section                          | (8) 265/70R x 19.5 Radial Tires                             | (8) 265/70R x 19.5 Radial Tires                             | (8) 265/70R x 19.5 Radial Tires                             |
| Tire Size - Wings                                   | (8) 320/70R x 15 Radial Tires                               | (8) 410/50R x 16.5 Radial Tires                             | (8) 410/50R x 16.5 Radial Tires                             |
| Wheel Hubs - Center Section                         | 8-Bolt  | 8-Bolt  | 8-Bolt  |
| Wheel Hubs - Wings                                  | 8-Bolt  | 8-Bolt  | 8-Bolt  |
| Spindles - Center Section                           | 4 in. (102 mm) Slip-In Spindles                             | 4 in. (102 mm) Slip-In Spindles                             | 4 in. (102 mm) Slip-In Spindles                             |
| Spindles - Wings                                    | 3 in. (76.2 mm) Slip-In Spindles                            | 3 in. (76.2 mm) Slip-In Spindles                            | 3 in. (76.2 mm) Slip-In Spindles                            |
| Hitch Type  | Self-Leveling with Hydraulic Adjustment                     | Self-Leveling with Hydraulic Adjustment                     | Self-Leveling with Hydraulic Adjustment                     |
| Hitch Category                                      | Cat. IV Cast Single Lip Ball Hitch                          | Cat. IV Cast Single Lip Ball Hitch                          | Cat. IV Cast Single Lip Ball Hitch                          |
| Machine Depth Control                               | Single Point, Front Mounted                                 | Single Point, Front Mounted                                 | Single Point, Front Mounted                                 |
| Wing Gauge Wheels - Swivel Type                     | (4) Standard  | (4) Standard  | (4) Standard  |
| Safety Chain, LED Warning Lights & SMV Emblem       | Standard  | Standard  | Standard  |
| Adjustment Wrenches                                 | Standard  | Standard  | Standard  |
| Powder Coat Paint, Blue Sapphire                    | Standard  | Standard  | Standard  |
| Spare Tire and Wheel Assembly                       | Optional  | Optional  | Optional  |
| HD Disc Blade Scrapers in lieu of Standard Scrapers | Optional for 26 in. x 0.25 in. Blades                       | Optional for 26 in. x 0.25 in. Blades                       | Optional for 26 in. x 0.25 in. Blades                       |
| HD Gauge Wheels in lieu of Standard                 | Optional  | Optional  | Optional  |
| Cat. V Cast Single Lip Ball Hitch                   | Optional  | Optional  | Optional  |
| Rear Tow Hitch with Hydraulic Hoses                 | Optional  | Optional  | Optional  |
| Chevron Conditioner Reels                           | Optional  | Optional  | Optional  |
| 3-Row Coil Tine Harrow                              | Optional  | Optional  | Optional  |
| Hydraulic Reel Lift                                 | Optional  | Optional  | Optional  |
| Horsepower Requirements                             | 8 to 10 HP (6 to 7 kw) per Foot                             | 8 to 10 HP (6 to 7 kw) per Foot                             | 8 to 10 HP (6 to 7 kw) per Foot                             |