



# 6' Till 'N Seed® Specifications

Product Attributes	BPSB-6
Approximate Weight (Empty)	2,120 lbs. (962 kg)
Three-Point Hitch Type	Cat. I, II, Quick-Attach, iMatch Compatible
Tractor Horsepower Range	35 to 60 HP (26 to 45 kw)
Tractor Lift Capacity Requirement	2,150 lbs. (977 kg) 24 in. (610 mm) Behind Lift Arms
Overall Width	90 in. (2.29 m)
Working Width	72 in. (1.83 m)
Base Unit Length	46 in. (1.17 m)
Unit Height	50 in. (1.27 m)
Recommended Speed	4 to 8 MPH (6.4 to 12.9 km/h) (Dependent on Conditions)
Acres/Hour	2.9 at 4 MPH, 5.8 at 8 MPH
Rotor Axles	1.75 in. (44.45 mm) Square Shaft
Rotor & Roller Bearings	1.5 in. (38.1 mm) Greaseable Bearings
Drive Rotor (Front)	414 lbs. (193 kg)
Number of Blades	31
Blade Material	Abrasion Resistant Steel
Blade Spacing	2.25 in. (57.15 mm)
Blade Thickness	0.313 in. (7.95 mm)
Blade Diameter	13 in. (330.2 mm) OD
Drive Type	Ground
Tillage Rotor (Middle)	351 lbs. (166 kg)
Number of Blades	32
Blade Material	Abrasion Resistant Steel
Blade Spacing	2.25 in. (57.15 mm)
Blade Thickness	0.188 in. (4.78 mm)
Blade Diameter	13 in. (330.2 mm) OD
Drive Ratio	2:01
Rotor Speed	197 RPM at 4 MPH, 394 RPM at 8 MPH
Independent Flotation	Standard
Down Force Adjustability	Standard
Drive Type	Number 80 Roller Chain
Firming Roller (Rear)	231 lbs. (105 kg)
Number of Cast Wheels	37
Independent Flotation	Standard
Air Shock	Standard
Air Pressure Range	20 to 120 psi (138 to 827 KPa)
Frame Construction	All Welded Structural Steel
Seed Box	Standard - Front & Rear
Seed Box Capacity	4.5 Bushels (158.5 l) + 1.4 Bushels (49.3 l)
Seed Metering	High Capacity Micro-Meter/Standard Micro-Meter
Seed Metering Drive	Positive Ground Driven
Drive Type	Roller Chain
Electronic Acre Meter	Optional
Powder Coat Paint, Red	Standard